



32" 2500 nit Professional High Brightness LCD

Model DS321LR4

The DS321LR4 is a 32 inch professional ultra high brightness LCD. With a brightness rating of 2,500 cd/m² this display features an LED back light for incredible, high contrast picture quality and low power consumption.

Designed for 24/7 operation the screen can be used in Landscape or Portrait orientation. The full HD resolution screen is colour calibrated to D6500k out of the box for natural, accurate colur reproduction.


Key Features


- 2,500 nit Maximum Brightness
- LED Backlight
- D65 Colour Calibrated
- 1,000,000:1 Dynamic Contrast Ratio
- Multiple Language Support
- 1920 x 1080 Native Resolution


32" 2500 nit Professional High Brightness LCD


Model DS321LR4

PANEL	
LCD Panel Type	31.5 inches TFT LCD
Native Resolution	1920 x 1080
Backlight	Direct LED
Brightness	2500 nit
Default Color Temperature	D65 (6500 K)
Contrast Ratio	10,000:1 (static), 1,000,000:1 (dyn)
Response Time	8 ms (typ)
Viewing Angle	178° / 178°
Light Life Time	50,000 hrs (typ.)
Panel Surface	AG Haze 11%, 3H
POWER	
Power Supply	Internal
Rated Voltage	100 V ~ 240 V, 50 Hz / 60 Hz
Power On Mode	115 W (typ), 190 W (max)
Power Saving Mode	< 5 W
_	
MECHANICAL SPECS	
Bezel Width (T/B/L/R)	28.6 / 21.4 / 15 / 15
Cabinet Color	Black
Monitor Dimension (LxHxD, w/o stand)	732 x 447 x 96 mm
Monitor Weight (set/package)	15.2 kg / 18.2 kg
VESA Mounting (dimension)	200 x 200 mm
Orientation	Portrait / Landscape
USER INTERFACE	
Language	English / French / Spanish
On/Off Scheduling	Yes
Ambient Light Sensor	Yes
I/O PORTS	
	In (x1): 640x480, 720x480, 800x600,
DM-D	1024x768, 1280x720, 1280x768, 1360x768,
	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080
VGA	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1
VGA USB	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1
VGA USB RS-232	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector
VGA USB	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1
VGA USB RS-232 RJ-45	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector
VGA USB RS-232 RJ-45	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector Wafer 6Pin 2.0mm Connector
VGA USB RS-232 RJ-45 ACCESSORIES Remote Control	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector Wafer 6Pin 2.0mm Connector
VGA USB RS-232 RJ-45 ACCESSORIES Remote Control Users Guide / Driver CD-ROM	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector Wafer 6Pin 2.0mm Connector
VGA USB RS-232 RJ-45 ACCESSORIES Remote Control Users Guide / Driver CD-ROM Video Cable	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector Wafer 6Pin 2.0mm Connector
VGA USB RS-232 RJ-45 ACCESSORIES Remote Control Users Guide / Driver CD-ROM Video Cable Power Cable	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector Wafer 6Pin 2.0mm Connector Yes Yes DM Yes
VGA USB RS-232 RJ-45 ACCESSORIES Remote Control Users Guide / Driver CD-ROM Video Cable	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector Wafer 6Pin 2.0mm Connector
VGA USB RS-232 RJ-45 ACCESSORIES Remote Control Users Guide / Driver CD-ROM Video Cable Power Cable RJ-45 Cable	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector Wafer 6Pin 2.0mm Connector Yes Yes DM Yes
VGA USB RS-232 RJ-45 ACCESSORIES Remote Control Users Guide / Driver CD-ROM Video Cable Power Cable RJ-45 Cable ENVIRONMENT	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector Wafer 6Pin 2.0mm Connector Yes Yes DM Yes Yes
VGA USB RS-232 RJ-45 ACCESSORIES Remote Control Users Guide / Driver CD-ROM Video Cable Power Cable RJ-45 Cable ENVIRONMENT Operating Temperature	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Waffer 6Pin 2.0mm Connector Waffer 6Pin 2.0mm Connector Yes Yes DM Yes Yes C ~ 40° C
VGA USB RS-232 RJ-45 ACCESSORIES Remote Control Users Guide / Driver CD-ROM Video Cable Power Cable RJ-45 Cable ENVIRONMENT	1024x768, 1280x720, 1280x768, 1360x768, 1920x1080 x1 x1 Wafer 6Pin 2.0mm Connector Wafer 6Pin 2.0mm Connector Yes Yes DM Yes Yes









For more information please contact:

All specifications subject to change without notice.

CE / FCC / ROHS



Pixelution Ltd.

Suite 4, 34 Bancroft, Hitchin, Hertfordshire, SG5 1LA

Tel: +44 1462 433558

Email: info@pixelution.co.uk